
## YAMUNA DENSONS Stress Control Mastic Tape (Yellow)



## **Features:**

- Void Filling
- Stress Relief
- Self Fusing
- Water Proof
- Self Amalgamating

## **Specifications:**

Stress Control Mastic Tape (Yellow)

Code	Width (mm)	Thickness (mm)	Length (mm)
DSCM120	20 ± 1	2 ± 0.2	120 ± 5
DSCM150	20 ± 1	2 ± 0.2	150 ± 5
DSCM180	20 ± 1	2 ± 0.2	180 ± 5
DSCM500	30 ± 1	2 ± 0.2	200 ± 5

## Technical Data for Black Mastic Tape

Property	Requirements	Test Method
Low Temperature Flexibility (4 hrs at -20 C)	No Cracking	ENATS 09 13
Continuous Operating Temperature	No Splitting, Cracking, Dripping or	ENATS 09 13
	Following at 100 C.	
Ultimate Elongation	300% (min.)	ASTM D 412
Visual Examination	Free From Pin Holes, Cracks, Inclusions	
	& Other Visible Defects	
Volume Resistivity	1 x 10 <sup>9</sup> ohm cm. (min.)	ASTM D 257
our Yellow		
Water Absorption	0.5% (max)	ENATS 09 13