

## YAMUNA DENSONS Heavy Duty Tinned Copper Lugs (Crimping type)



### Dimensions of Heavy Duty Tinned Copper Lugs

Size mm <sup>2</sup>	(Ø)A ±0.3	(Ø)C ±0.3	J ±3	D ±1	E ±0.2	K ±1	H ±1	G ±1
2.5	2.4	4.0	18	10	4.2	2	6	5
4	3.1	4.8	20	10	4.2	2	6	5
6	3.8	5.5	23	10	4.2	3	9	6
10	4.5	6.2	25	12	6.4	3	9	6
16	5.4	7.1	36	12	6.4	4	9	7
25	6.8	8.8	40	13	6.4	4	11	10
35	8.2	10.6	48	15	6.4	5	11	10
50	9.5	12.4	59	18	6.4	6	13	11
70	11.2	14.7	61	21	12.8	7	13	12
95	13.5	17.4	68	25	12.8	9	13	13
120	15.0	19.4	73	28	12.8	10	14	14
150	16.5	21.2	86	30	13.0	11	17	17
185	18.5	23.5	89	34	16.2	12	17	17
240	21.0	26.5	104	38	16.2	14	21	21
300	23.5	30.0	115	43	16.2	15	23	23
400	26.8	34.8	136	50	17.0	18	26	26
500	30.0	39.0	148	56	21.0	20	28	28
630	35.0	45.0	172	65	21.0	22	33	33
800	39.0	50.6	209	73	-	17	40	35
1000	43.0	56.2	245	81	-	20	45	45

(all dimensions are in mm)

### Features :

- Conductivity 99.9% (IACS)
- Long barrel